Pearlpaint Color Mixing System SB65 Violet [8665]

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 7/5/2024 Revision date: 9/28/2025 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Pearlpaint Color Mixing System SB65 Violet [8665]
Product code : F.8600SB65

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use,Industrial use
Use of the substance/mixture : Dyestuff/pigment

1.3. Details of the supplier of the safety data sheet

Manufacturer
PearlPaint Group
Larserpoortweg 20
8218 NK Lelystad
P.O. Box 2365
8203 AH Lelystad
Nederland
T +31 (0)320-285 353
info@pearlpaintgroup.com, www.pearlpaintgroup.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC)	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin sensitisation, Category 1	H317
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS02 GHS07

CLP Signal word	:	Warning
Contains	:	2-methoxy-1-methylethyl acetate; n-butyl acetate
Hazard statements (CLP)	:	H226 - Flammable liquid and vapour. H317 - May cause an allergic skin reaction. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	:	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing vapours, spray. P280 - Wear protective gloves, eye protection. P312 - Call doctor if you feel unwell. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.
EUH-statements	:	EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LU, LV, MT, NL, PL, RO, SE, SI, SK, IS, NO, RS, CH); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336
n-butyl acetate substance with national workplace exposure limit(s) (CZ, DE, FR, GB, NL, PL, RO, SK, RS); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
	CAS-No.: 1259547-09-5	2.5 – 3	Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	:	Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	:	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	:	Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	:	Rinse eyes with water as a precaution.
First-aid measures after ingestion	:	Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	:	May cause drowsiness or dizziness.

Symptoms/effects after inhalation	:	Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	:	May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	:	None under normal conditions.
Symptoms/effects after ingestion	:	None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	:	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	:	Flammable liquid and vapour.
Explosion hazard	:	No direct explosion hazard.
Hazardous decomposition products in case of fire	:	Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	:	Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	:	Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	:	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	:	Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures	:	Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Ground/bond container and receiving equipment.
Storage conditions	:	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials	:	Always store product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m³
	50 ppm
IOEL STEL	550 mg/m³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands - Occupational Exposure Limits	
Local name	1-Methoxy-2-propylacetaat
TGG-8u (OEL TWA)	550 mg/m³
	100 ppm
Regulatory reference	Arbeidsomstandighedenregeling 2024

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-butyl acetate
IOEL TWA	241 mg/m³
	50 ppm
IOEL STEL	723 mg/m³

n-butyl acetate (123-86-4)	
	150 ppm
Remark	SCOEL Recommendations (Ongoing)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Netherlands - Occupational Exposure Limits	
Local name	n-Butylacetaat
TGG-8u (OEL TWA)	241 mg/m³
	50 ppm
TGG-15min (OEL STEL)	723 mg/m³
	150 ppm
Regulatory reference	Arbeidsomstandighedenregeling 2024

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:
Wear recommended personal protective equipment.
Personal protective equipment symbol(s):

Eye and face protection

Eye protection:
Safety glasses

Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Violet.
Appearance	:	Liquid.
Odour	:	Solvent like odour.
Odour threshold	:	Not available
Melting point	:	Not applicable

Freezing point	:	Not available
Boiling point	:	120 (120 – 128) °C
Flammability	:	Flammable liquid and vapour.
Lower explosion limit	:	1.2 vol %
Upper explosion limit	:	7.5 vol %
Flash point	:	39 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	> 20.5 mm²/s
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	15 hPa
Vapour pressure at 50°C	:	Not available
Density	:	1.05 (0.95 – 1.15) kg/l
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Pearlpaint Color Mixing System SB65 Violet [8665]	
LD50 oral rat	6112 mg/kg
LD50 dermal rabbit	12589 mg/kg
LC50 Inhalation - Rat	19200 mg/l
ATE CLP (vapours)	19200 mg/l/4h

Pearlpaint Color Mixing System SB65 Violet [8665]	
ATE CLP (dust,mist)	19200 mg/l/4h

2-methoxy-1-methylethyl acetate (108-65-6)	
LD50 oral	8532 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	35.7 mg/l

n-butyl acetate (123-86-4)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 14000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h

Skin corrosion/irritation : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)	
pH	4

n-butyl acetate (123-86-4)	
pH	6.2

Serious eye damage/irritation : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)	
pH	4

n-butyl acetate (123-86-4)	
pH	6.2

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

2-methoxy-1-methylethyl acetate (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	2.4 mg/l/6h/day

Aspiration hazard : Not classified

Pearlpaint Color Mixing System SB65 Violet [8665]	
Viscosity, kinematic	> 20.5 mm²/s

n-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Not classified

2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	373 mg/l
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

n-butyl acetate (123-86-4)	
LC50 - Fish [1]	81 (18 – 185) mg/l
LC50 - Fish [2]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	200 mg/l
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Pearlpaint Color Mixing System SB65 Violet [8665]	
Persistence and degradability	Rapidly degradable

2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Rapidly degradable

n-butyl acetate (123-86-4)	
Persistence and degradability	Rapidly degradable

(1259547-09-5)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate (108-65-6)	
Partition coefficient n-octanol/water (Log Pow)	1.2

n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	2.3

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Flammable vapours may accumulate in the container. Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / RID

ADR	RID
14.1. UN number or ID number	
Not applicable	Not applicable
14.2. UN proper shipping name	
Not applicable	Not applicable
14.3. Transport hazard class(es)	
Not applicable	Not applicable
14.4. Packing group	
Not applicable	Not applicable
14.5. Environmental hazards	
Not applicable	Not applicable
No supplementary information available	

14.6. Special precautions for user

Overland transport
Not applicable

Rail transport
Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Netherlands

ABM category	:	B(4) - low hazard for aquatic organisms
SZW-lijst van kankerverwekkende stoffen	:	None of the components are listed
SZW-lijst van mutagene stoffen	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	:	None of the components are listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

Abbreviations and acronyms:	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.

Full text of H- and EUH-statements:	
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method

Safety Data Sheet applicable for regions : NL - Netherlands

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.